




VARIABLE
DISPLACEMENT
AXIAL PISTON
PUMPS

DVP SERIES

GENERAL INFORMATIONS / INSTRUCTIONS

This variable displacement piston pump has **dual flow** and an additional piggybacked gear pump for auxiliary service, open center circuits. The pump has been designed specifically for **mini excavators** where compactness and ease of installation are critical. The automatic overall torque limiter allows you to optimize the performance of the machine while saving energy. An additional gear unit to supply joystick functions is also available.

DISPLACEMENTS

Piston units

From 7,8 cm³/rev (0.48 in³/rev)

To 15 cm³/rev (0.91 in³/rev)

Gear units

From 4,95 cm³/rev (0.30 in³/rev)

To 21,14 cm³/rev (1.29 in³/rev)

MAX SPEED

2600 min⁻¹


APPLICATION

Medium pressure

SECTOR

Mobile

- Compact design
- Low noise emission
- Energy savings
- Long service life



1	Pump body
2	Spring guide
3	Main pilot spring
4	Cover
5	Pilot piston
6	Pump body Kappa 20
7	Retaining plate
8	Cylinders block
9	Pistons
10	Pistons guide plate
11	Swash plate

03/07.2016



Modification from former edition.

GENERAL INFORMATIONS / INSTRUCTIONS

DIRECTION OF ROTATION

Clockwise defined looking at the drive shaft.

HYDRAULIC FLUID

Mineral oil based hydraulic fluid HL or HLP type conforming to DIN 51524. For the use of ecological fluids, HF fluid or HWBF fluid, please consult our sales department. The system should be designed to prevent aeration of the hydraulic fluid.

FLUID VISCOSITY

The fluid viscosity range for optimal use of DVP pump is between 15 and 35 cSt (77 and 163 SSU).

Functional limit conditions are:

max.: 1000 cSt (4546 SSU) at start up at -25 °C (-13 °F) with straight and short inlet line.

min.: 10 cSt (58 SSU) at maximum temperature of 100 °C (212 °F)

FILTRATION

To ensure the optimal performance and the maximum life to the pump, the hydraulic fluid must have and maintain a fluid contamination within the values shown in the table below.

Working pressure psi (bar)	$\Delta p < 140$ (2030)	$140 < \Delta p < 210$ (2030) (3045)	$\Delta p > 210$ (3045)
Contamination class NAS 1638	9	8	7
Contamination class ISO 4406:1999	20/18/15	19/17/14	18/16/13
Achieved with filter $\beta_{x(0)} \geq 75$ according to ISO 16889	10 μm	10 μm	10 μm

Casappa recommends to use its own production filters:



STORAGE

The storage must be in a dry environment.

Max storage time in ideal conditions is 24 months.

The ideal storage temperature is between 5°C (41°F) and 20°C (68°F). No problem in case of temperature between -40°C (-40°F) and 50°C (122°F). Below -40°C (-40°F) please consult our technical sales department.

INSTALLATION

Check that the maximum coupling eccentricity stays within 0,25 mm (0.0098 in) to reduce shaft loads due to misalignment. It is advised to use a flexible coupling suitable to absorb eventual rotational shock. The direction of rotation of the pump must agree with the prime mover rotation. Before installation, the case of the pump must be filled with fluid.

LINES

The lines must have a major diameter which is at least as large as the diameter of pump ports, and must be perfectly sealed. To reduce loss of power, the lines should be as short as possible, reducing the sources of hydraulic resistance (elbow, throttling, gate valves, etc.) to a minimum. A length of flexible tubing is recommended to reduce the transmission of vibrations.

Before connecting the lines, remove any plug and make sure that the lines are perfectly clean. Check that the dimensions of the suction line guarantee a pressure equal or superior to 0,8 bar (24 in Hg). Inlet pressure less than 0,8 bar (24 in Hg) could cause an increase of noise emission, the decrease of the pump performances and a reduction of its life expectancy.

STARTING UP

Check that all connections are secure and that the entire system is completely clean. Add oil to the tank always using a filter. Bleed the air from the circuit to help the filling. Turn on the system for a few moments at minimum speed, then bleed the circuit again and check the level of oil in the tank. Gradually increase the pressure and speed of rotation up to the pre-set operating levels, which must stay within the stated limits as specified in the catalogue.

Replaces: 02/04.2013

03/07.2016

TECHNICAL DATA

Technical data with mineral oil

HL or HLP mineral oil based hydraulic fluid to DIN 51524

Inlet pressure	in Bar abs. (Hg)	min.	0,7 (21)
	bar abs. (psi)	max.	3 (44)
Max. speed n _{max}	min ⁻¹	@ V _{max}	2600
Control type	Constant torque control		
Setting torque range	Nm (lbf in)		from 39 (345) to 120 (1062)
Drain line	Internal		
Fill capacity	l (US gallon)		0,9 (0.2)
Mass (without oil)	kg (lbs)		from 19,5 (43) to 20,5 (45.2)
Seals	N = Buna		
Operating temperature 	°C (°F)	min.	-25 (-13)
		max. cont.	80 (176)
		max. peak	100 (212)

Piston units type

DVP

Max. displacement (standard)	cm^3/rev (in^3/rev)	V_{max}	15 (0.91)	14 (0.85)	12,5 (0.76)	11 (0.67)	10 (0.61)	9 (0.55)	8,5 (0.52)	8 (0.49)	7,8 (0.48)
Min. displacement (standard)		V_{min}	4 (0.24) - 3,6 (0.22) - 3 (0.18) - 2,7 (0.16)								
Max. outlet pressure	bar (psi)	cont.	210 (3045)								
		int.	230 (3335)								
		peak	250 (3625)								
Max. delivery (theor.)	l/min (US gpm)	@ $V_{max} - n_{max}$	39 (10.3)	36,4 (9.6)	32,5 (8.6)	28,6 (7.6)	26 (6.9)	23,4 (6.2)	22,1 (5.84)	20,8 (5.50)	20,2 (5.34)

KAPPA gear units

20-4 20-6,3 20-8 20-11,2 20-14 20-16 20-20

Displacement	cm^3/rev (in^3/rev)	V	4,95 (0.30)	6,61 (0.40)	8,26 (0.50)	11,23 (0.69)	14,53 (0.89)	16,85 (1.03)	21,14 (1.29)
Max. outlet pressure	bar (psi)	cont.	285 (4133)	285 (4133)	285 (4133)	275 (3988)	265 (3843)	260 (3770)	210 (3045)
		int.	300 (4350)	300 (4350)	300 (4350)	290 (4205)	290 (4205)	290 (4205)	290 (4205)
		peak	330 (4785)	330 (4785)	330 (4785)	320 (4640)	320 (4640)	320 (4640)	250 (3625)
Max. delivery (theor.)	l/min (US gpm)	@ $V - n_{max}$	12,8 (3.38)	17,1 (4.52)	21,4 (5.65)	29,2 (7.7)	37,7 (10.0)	43,8 (11.6)	54,9 (14.5)

POLARIS gear units

20-4

Displacement	cm^3/rev (in^3/rev)	V	4,95 (0.30)
Max. outlet pressure	bar (psi)	cont.	250 (3625)
		int.	280 (4060)
		peak	300 (4350)

For different working conditions, please consult our sales department.

Replaces: 02/04.2013



03/07.2016

DIMENSIONS

DVP

Available also with built-in valves for different purposes.
For more information please consult our sales department.

Replaces: 02/04.2013



DCAT_039_001_65300016

03/07.2016

KAPPA gear units

DVP piston units	20•4	20•6,3	20•8	20•11,2	20•14	20•16	20•20	Dimensions	
7,8 - 8 - 8,5	240,2	242,7	245,2	248,7	252,7	258,2	264,7	mm	A
9 - 10	(9.4567)	(8.3740)	(9.6535)	(9.7913)	(9.9488)	(10.1654)	(10.4213)	(inch)	
11 - 12,5	212,7	215,2	217,7	221,2	219,7	225,2	231,7	mm	B
14 - 15	(8.3740)	(8.4724)	(8.5709)	(8.7087)	(8.6496)	(8.8661)	(9.1220)	(inch)	


To order please consult our sales department.

SHAFTS / MOUNTING FLANGES

SAE "B" SPLINE

04


Available with flange code **S5**



SAE "B" 2 HOLES

S5


SAE J744




SPLINE

F8

Available with flange code **S5**




DCAT_039_003_48417003



SPLINE

C1

Available with flange code **S5**



01/11.2007

PORTS SIZE



Tightening torque for low pressure side port.



Tightening torque for high pressure side port (values obtained at 350 bar)

Replaces: 01/11.2007


INLET PORT

SAE FLANGED PORTS J518 - Standard pressure series 3000 PSI

SSM

Metric thread ISO 60° conforms to ISO/R 262

CODE	Nominal size	Pump type	Nm (lbf in)
MD	1" 1/4	DVP	20 ⁺¹ (177 ÷ 186)




OUTLET PORTS

GAS STRAIGHT THREAD PORTS

BSPP

British standard pipe parallel (55°) conforms to UNI - ISO 228



O

CODE	Nominal size	Pump type	A	Ø B	Ø C	D	E	Nm (lbf in)
			mm (in)	mm (in)	mm (in)	mm (in)	mm (in)	
GC	3/8"	PL20	G 3/8	30 (1.1811)	15 (0.5906)	14 (0.5512)	0,5 (0.0197)	25 ⁺¹ (221 ÷ 230)
GD	1/2"	DVP	G 1/2	30 (1.1811)	19 (0.7480)	17 (0.6693)	2 (0.0787)	50 ^{+2,5} (443 ÷ 465)
		KP20		—	—	20 (0.7874)	—	50 ^{+2,5} (443 ÷ 465)

DVP outlet port

02/04.2013

PORTS SIZE

 Tightening torque for low pressure side port.


 Tightening torque for high pressure side port (values obtained at 350 bar)

SAE STRAIGHT THREAD PORTS J514

ODT

American straight thread UNC-UNF 60° conforms to ANSI B 1.1

CODE	Nominal size	Pump type	 Nm (lbf in)
OC	5/8"	DVP KP20	70 ⁺⁵ (620 ÷ 664)




Replaces: 01/11.2007

JIS B2351 STRAIGHT THREAD PORTS

JIS

British standard pipe parallel (55°) conforms to UNI - ISO 228




CODE	Nominal size	Pump type	A mm (in)	Ø B mm (in)	Ø C mm (in)	D mm (in)	E mm (in)	 Nm (lbf in)
JC	3/8"	PL20	PF 3/8	28	15	18	0,5	25 ⁺¹
		KP20	(G 3/8)	(1.1024)	(0.5906)	(0.7087)	(0.0197)	(221 ÷ 230)
		DVP					2 (0.0787)	50 ^{+2,5} (443 ÷ 465)
JD	1/2"	PL20	PF 1/2	34	19	18	0,5	50 ^{+2,5}
		KP20	(G 1/2)	(1.3386)	(0.7480)	(0.7087)	1 (0.0394)	(443 ÷ 465)

02/04.2013


BREATHER PLUG AND MOUNTING POSITIONS (ONLY ON REQUEST)

Breather plug is available only on request.
For more information please consult our sales department.


STANDARD POSITION



REAR POSITION



SIDE POSITION





01/11.2007



OTHER COMBINATIONS

The pump is standard with common inlet.
For more information please consult our sales department.

DVP + PLP10





DVP + PLP20 TWIN





Replaces: 01/11.2007

DVP + KP20 + PLP10



DVP + KP20 + PLP20



02/04.2013



HYDRAULIC
GEAR
PUMPS

INDEX

Section	Description	Page
FEATURES		2
	PERFORMANCE CURVES	9
SINGLE GEAR PUMPS	FP 20	18
	FP 30	23
	FP 40	31
MULTIPLE GEAR PUMPS		37
PORTS CONNECTORS TIGHTENING TORQUE		65
	SUPPORT (ISO STANDARD)	66
SUPPORT	KIT TO ASSEMBLE FORMULA PUMPS WITH SUPPORT	67
	APPLICATIONS	68
CHANGING ROTATION		70
INSTRUCTIONS		71

Replaces: 01/08.2005

FEATURES

FORMULA designates a CASAPPA gear pump range specifically designed for applications requiring high pressure levels also at low speed; applications such as truck-mounted cranes, tripper trucks and lift-trucks etc. Special design features and an exclusive CASAPPA patent have perfected a sophisticated mechanism which makes FORMULA a highly reliable unit, proven by years of service in the specific field of use. The versatility offered by the range of Italian (triangular) European (ISO) and American (SAE) mounting flanges allows to the FORMULA pumps to be used in several applications.

DISPLACEMENTS

From 0.50 in³/rev (8,26 cm³/rev)

To 9.20 in³/rev (150,79 cm³/rev)

PRESSURE

Max. continuous 4205 psi (290 bar)

Max. intermittent 4568 psi (315 bar)


Max. di peak 4713 psi (325 bar)

MAX. SPEED

Max. 3000 min⁻¹

- Two piece cast iron housing
- High performance at very low speed
- Ideal for truck applications

1	Mounting flange
2	Seals
3	Gear
4	Body
5	Thrust plates
6	Shaft
7	Outboard bearing



03/05.2013



Modification from former edition.

FEATURES

WARNING !

Failure or improper use of the product can cause damage at the same product or system.

Make sure that this is the last issue.

Replaces: 02/07.2008

Construction	External gear type pumps
Mounting	ISO (ZF), ITALIAN (triangular) and SAE flanges
Line connections	Screw
Direction of rotation (looking at the drive shaft)	Anti-clock (S) - clockwise (D) - reversible (R or B)
Inlet pressure range for pumps	10 ÷ 44 psi - [0,7 ÷ +3 bar (abs.)]
Fluid temperature range	See table (1)
Fluid	Mineral oil based hydraulic fluids to ISO/DIN and fire resistant fluids [see table (1)]. For other fluids please consult our technical sales department.
Viscosity range	From 60 to 456 SSU [12 to 100 mm ² /s (cSt)] recommended Up to 3410 SSU [750 mm ² /s (cSt)] permitted
Filtering requirement	See table (2)
Antioxidant protection	Red paint IC105

Tab. 1

Type	Fluid composition	Max pressure psi - (bar)	Max speed min ⁻¹	Temperature °F - (°C)			Seals (◆)
				Min	Max continuous	Max peak	
ISO/DIN	Mineral oil based hydraulic fluid to ISO/DIN	See page 5 - 6 - 7	See page 5 - 6 - 7	-13 (-25)	176 (80)	212 (100)	N
				-13 (-25)	230 (110)	257 (125)	V
HFA	Oil emulsion in water 5 ÷ 15% of oil	725 (50)	1500	36 (2)	131 (55)	—	N
HFB	Water emulsion in oil 40 % of water	1740 (120)	1500	36 (2)	140 (60)	—	N
HFC	Water - glycol	1450 (100)	1500	-4 (-20)	140 (60)	—	N Bz
HFD	Phosphate ester (●)	2175 (150)	1500	14 (-10)	176 (80)	—	V Bz

(◆) **N** = Buna N (standard) - **V** = Viton - **N Bz** = Buna N and Bronze thrust plates - **V Bz** = Viton and Bronze thrust plates.

(●) For skydrol phosphate esters please consult our technical sales department.

03/05.2013

Tab. 2


Working pressure psi (bar)	$\Delta p < 2030$ (140)	$2030 < \Delta p < 3045$ (140) (210)	$\Delta p > 3045$ (210)
Contamination class NAS 1638	10	9	8
Contamination class ISO 4406:1999	21/19/16	20/18/15	19/17/14
Achieved with filter $\beta_{10(c)} \geq 200$ according to ISO 16889	—	10 μ m	10 μ m
Achieved with filter $\beta_{25(c)} \geq 200$ according to ISO 16889	25 μ m	—	—

Casappa recommends to use its own production filters:




FEATURES


DEFINITION OF ROTATION DIRECTION LOOKING AT THE DRIVE SHAFT



ANT-CLOCK ROTATION




CLOCKWISE ROTATION



REVERSIBLE ROTATION

PRESSURE DEFINITION



p_1 Max. continuous pressure
 p_2 Max. intermittent pressure
 p_3 Max. peak pressure

GENERAL NOTES

Available with different inlet and outlet ports. Standard pumps are equipped with BUNA N (N) seals, for particular operating conditions (V) VITON seals and BUNA or VITON seals with bronze thrust plates (N Bz), (V Bz) are available. If you use fire resistant fluids specify the type of them at the order. For more information please consult our technical sales department.

01/08.2005

FORMULA 20 GENERAL DATA PUMPS

FP 20

Pump type	Displacement in ³ /rev (cm ³ /rev)	Max. pressure			Intermittent max. speed		Min. speed
		p ₁	p ₂	p ₃	At p ₂ press.	Without load	At p ₂ press.
		psi (bar)			min ⁻¹		
FP 20•8 (•)	0.50 (8,26)	4060 (280)	4495 (310)	4713 (325)	2000	4200	300
FP 20•11,2 (•)	0.69 (11,23)	4060 (280)	4495 (310)	4713 (325)	2000	4200	300
FP 20•16	1.03 (16,85)	4060 (280)	4495 (310)	4713 (325)	2000	4200	300
FP 20•20	1.29 (21,14)	3770 (260)	4060 (280)	4205 (290)	2000	4200	300
FP 20•25	1.61 (26,42)	3190 (220)	3625 (250)	3770 (260)	2000	4200	300
FP 20•31,5	2.01 (33,03)	2755 (190)	3045 (210)	3190 (220)	1800	4000	300
FP 20•36 (•)	2.19 (35,94)	2465 (170)	2755 (190)	2900 (200)	1800	4000	300
FP 20•40	2.42 (39,64)	2320 (160)	2610 (180)	2755 (190)	1800	4000	300

(•) Only available in ISO 16 Z0 and ITALIAN 13 T1 version.

p₁= Max. continuous pressure

p₂= Max. intermittent pressure

p₃= Max. peak pressure

The values in the table refer to unidirectional and reversible pumps.

01/08.2005

FORMULA 30 GENERAL DATA PUMPS
FP 30

Pump type	Displacement in ³ /rev (cm ³ /rev)	Max. pressure			Intermittent max. speed		Min. speed
		p ₁	p ₂	p ₃	At p ₂ press.	Without load	At p ₂ press.
		psi (bar)			min ⁻¹		
FP 30•17	1.05 (17,28)	4205 (290)	4568 (315)	4713 (325)	3000	4000	300
FP 30•27	1.63 (26,70)	4205 (290)	4568 (315)	4713 (325)	3000	4000	300
FP 30•34	2.11 (34,56)	4060 (280)	4350 (300)	4495 (310)	2800	4200	300
FP 30•38	2.40 (39,27)	4060 (280)	4350 (300)	4495 (310)	2800	3500	300
FP 30•43	2.68 (43,98)	3915 (270)	4205 (290)	4350 (300)	2500	3500	300
FP 30•51	3.16 (51,83)	3480 (240)	3770 (260)	4060 (280)	2500	3500	300
FP 30•61	3.74 (61,26)	3190 (220)	3480 (240)	3625 (250)	2000	3500	300
FP 30•73	4.50 (73,82)	2900 (200)	3190 (220)	3335 (230)	1800	3500	300
FP 30•82	4.98 (81,68)	2755 (190)	3045 (210)	3190 (220)	1800	3500	300
FP 30•100	6.16 (100,52)	2610 (180)	2900 (200)	3190 (220)	1800	3500	300
FP 30•125	7.67 (125,66)	2320 (160)	2610 (180)	2900 (200)	1800	3500	300

 p₁= Max. continuous pressure

 p₂= Max. intermittent pressure

 p₃= Max. peak pressure

The values in the table refer to unidirectional pumps.
 Reversible pump max pressures are 15% lower than those shown in table.
 For different working conditions please consult our sales department.

T2 type double shaft flange allow the pumps to work in clockwise or anticlockwise rotation obtaining the reversible advantages and maintaining the general data of unidirectional pumps.

01/08.2005

FORMULA 40 GENERAL DATA PUMPS

FP 40

Pump type	Displacement in ³ /rev (cm ³ /rev)	Max. pressure			Intermittent max. speed		Min. speed
		p ₁	p ₂	p ₃	At p ₂ press.	Without load	At p ₂ press.
		psi (bar)			min ⁻¹		
FP 40•63	3.75 (61,43)	4205 (290)	4568 (315)	4713 (325)	2700	4200	300
FP 40•73	4.43 (72,60)	4060 (280)	4350 (300)	4568 (315)	2700	4200	300
FP 40•87	5.28 (86,56)	3770 (260)	4060 (280)	4205 (290)	2700	4000	300
FP 40•109	6.64 (108,90)	3480 (240)	3770 (260)	4060 (280)	2700	4000	300
FP 40•133	8.18 (134,03)	3190 (220)	3625 (250)	3770 (260)	2500	4000	300
FP 40•151	9.20 (150,79)	2610 (180)	3045 (210)	3190 (220)	2500	4000	300

p₁= Max. continuous pressure

p₂= Max. intermittent pressure

p₃= Max. peak pressure

The values in the table refer to unidirectional pumps.
 Reversible pump max pressures are 15% lower than those shown in table.
 For different working conditions please consult our sales department.

T2 type double shaft flange allow the pumps to work in clockwise or anticlockwise rotation obtaining the reversible advantages and maintaining the general data of unidirectional pumps.

01/08.2005

DESIGN CALCULATIONS FOR PUMPS

Q	US gpm (l/min)	Flow
M	lbf in(Nm)	Torque
P	HP (kW)	Power
V	in ³ /rev (cm ³ /rev)	Displacement
n	min ⁻¹	Speed
Δp	psi (bar)	Pressure
$\eta_v = \eta_v (V, \Delta p, n)$	($\approx 0,98$)	Volumetric efficiency
$\eta_{hm} = \eta_{hm} (V, \Delta p, n)$	($\approx 0,90$)	Mechanical efficiency
$\eta_t = \eta_v \cdot \eta_{hm}$	($\approx 0,88$)	Overall efficiency

Replaces: 01/08.2005


$$\begin{aligned}
 \text{○ } Q &= Q_{\text{theor.}} \cdot \eta_v \\
 Q_{\text{theor.}} &= \frac{V \text{ (cm}^3\text{/rev)} \cdot n \text{ (min}^{-1}\text{)}}{1000} \quad [\text{l/min}] \\
 M &= \frac{M_{\text{theor.}}}{\eta_{hm}} \quad [\text{Nm}] \\
 M_{\text{theor.}} &= \frac{\Delta p \text{ (bar)} \cdot V \text{ (cm}^3\text{/rev)}}{62,83} \\
 P_{\text{IN}} &= \frac{P_{\text{OUT}}}{\eta_t} \quad [\text{kW}] \\
 P_{\text{OUT}} &= \frac{\Delta p \text{ (bar)} \cdot Q \text{ (l/min)}}{600}
 \end{aligned}$$

○ 03/05.2013

Note: Diagrams providing approximate selection data will be found on subsequent pages.



FORMULA 20 GEAR PUMPS PERFORMANCE CURVES

FP 20



Each curve has been obtained at 122 °F (50°C), using oil with viscosity 168 SSU (36 cSt) at 104 °F (40°C) and at these pressures:


FP 20•8	— —	290 psi (20 bar)
	—	4060 psi (280 bar)
FP 20•11,2	— —	290psi (20 bar)
	—	4060 psi (280 bar)
FP 20•16	— —	290 psi (20 bar)
	—	4060 psi (280 bar)
FP 20•20	— —	290 psi (20 bar)
	—	3770 psi (260 bar)
FP 20•25	— —	290 psi (20 bar)
	—	3190 psi (220 bar)
FP 20•31,5	— —	290 psi (20 bar)
	—	2755 psi (190 bar)
FP 20•36	— —	290 psi (20 bar)
	—	2465 psi (170 bar)
FP 20•40	— —	290 psi (20 bar)
	—	2320 psi (160 bar)




FORMULA 20 GEAR PUMPS PERFORMANCE CURVES

FP 20


FP 20•16




FP 20•20



FP 20•25



FP 20•31,5




01/08.2005


FORMULA 20 GEAR PUMPS PERFORMANCE CURVES

FP 20

FP 20•36



FP 20•40




01/08.2005

FORMULA 30 GEAR PUMPS PERFORMANCE CURVES

FP 30

FP 30




Each curve has been obtained at 122 °F (50°C), using oil with viscosity 168 SSU (36 cSt) at 104 °F (40°C) and at these pressures:


○	FP 30•17	—	290 psi (20 bar)
		- -	4205 psi (290 bar)
	FP 30•27	—	290 psi (20 bar)
		- -	4205 psi (290 bar)
	FP 30•34	—	290 psi (20 bar)
		- -	4060 psi (280 bar)
	FP 30•38	—	290 psi (20 bar)
		- -	4060 psi (280 bar)
	FP 30•43	—	290 psi (20 bar)
		- -	3915 psi (270 bar)
	FP 30•51	—	290 psi (20 bar)
		- -	3480 psi (240 bar)
	FP 30•61	—	290 psi (20 bar)
		- -	3190 psi (220 bar)
	FP 30•73	—	290 psi (20 bar)
		- -	2900 psi (200 bar)
	FP 30•82	—	290 psi (20 bar)
		- -	2755 psi (190 bar)
	FP 30•100	—	290 psi (20 bar)
		- -	2610 psi (180 bar)
	FP 30•125	—	290 psi (20 bar)
		- -	2320 psi (160 bar)

Replaces: 01/08.2005

FP 30•17



FP 30•27




○ 03/05.2013


FORMULA 30 GEAR PUMPS PERFORMANCE CURVES

FP 30


FP 30•34




FP 30•38



FP 30•43



FP 30•51




01/08.2005


FORMULA 30 GEAR PUMPS PERFORMANCE CURVES

FP 30


FP 30•61




FP 30•73



FP 30•82



FP 30•100




01/08.2005

FORMULA 30 GEAR PUMPS PERFORMANCE CURVES

FP 30

FP 30•125




01/08.2005

FORMULA 40 GEAR PUMPS PERFORMANCE CURVES

FP 40


FP 40




Each curve has been obtained at 122 °F (50°C), using oil with viscosity 168 SSU (36 cSt) at 104 °F (40°C) and at these pressures:

○	FP 40•63	—	290 psi (20 bar)
		- -	4205 psi (290 bar)
	FP 40•73	—	290 psi (20 bar)
		- -	4060 psi (280 bar)
	FP 40•87	—	290 psi (20 bar)
		- -	3770 psi (260 bar)
	FP 40•109	—	290 psi (20 bar)
		- -	3480 psi (240 bar)
	FP 40•133	—	290 psi (20 bar)
		- -	3190 psi (220 bar)
	FP 40•151	—	290 psi (20 bar)
		- -	2610 psi (180 bar)

FP 40•63



FP 40•73




Replaces: 01/08.2005

○ 03/05.2013


FORMULA 40 GEAR PUMPS PERFORMANCE CURVES

FP 40


FP 40•87




FP 40•109



FP 40•133



FP 40•151



01/08.2005


FORMULA 20

HYDRAULIC GEAR PUMPS ISO STANDARD

16 Z0

GAS STRAIGHT THREAD PORTS

British standard pipe parallel (55°) conforms to UNI - ISO 228



Radial and/or axial load are not allowed.

Standard version pumps have reversible rotation and internal drain.

The drawing shows the version with rear ports.

Removing the lateral plugs all possible combination ports are allowed.

Screw tightening torque Nm (lbf in)

v

 $70^{+7} (558 \div 682)$

Pump type		A	B	C	Mass
		mm (in)	mm (in)		kg (lbs)
FP 20•8	B0-16Z0-(L)P GD/GD-N	104 (4.094)	80 (3.150)	G 1/2	5,31 (11.71)
FP 20•11,2		107,5 (4.232)	83,5 (3.287)		5,70 (12.57)
FP 20•16		117 (4.606)	87,5 (3.445)		6,00 (13.23)
FP 20•20		123,5 (4.862)	94 (3.701)		6,35 (14.00)
FP 20•25	B0-16Z0-(L)P GE/GE-N	131,5 (5.177)	87 (3.425)	G 3/4	6,80 (14.99)
FP 20•31,5		141,5 (5.571)	97 (3.819)		7,18 (15.83)
FP 20•36		146,4 (5.764)	91,4 (3.598)		7,44 (16.41)
FP 20•40		151,5 (5.965)	97 (3.819)		7,80 (17.20)

How to order:

FP 20•8 B0-16Z0-(L)P GD/GD-N


01/08.2005

FORMULA 20

HYDRAULIC GEAR PUMPS ITALIAN STANDARD

13 T1- L

GAS STRAIGHT THREAD PORTS
British standard pipe parallel (55°) conforms to UNI - ISO 228



Standard version pumps have reversible rotation and internal drain.

Screw tightening torque Nm (lbf in)

V

70 ^{±7} (558 ÷ 682)

01/08.2005

Pump type	A	B	C	Mass
	mm (in)	mm (in)		kg (lbs)
FP 20•8	132,5 (5.217)	105 (4.134)	G 1/2	4,8 (10.58)
FP 20•11,2	136 (5.354)	108,5 (4.272)		5 (11.03)
FP 20•16	145,5 (5.728)	112,5 (4.429)		5,2 (11.47)
FP 20•20	152 (5.984)	119 (4.685)		5,3 (11.69)
FP 20•25	160 (6.299)	112 (4.409)	G 3/4	5,9 (13.01)
FP 20•31,5	170 (6.693)	122 (4.803)		6 (13.23)
FP 20•36	175,5 (6.909)	116,5 (4.587)		6,3 (13.89)
FP 20•40	181 (7.126)	122 (4.803)		6,6 (14.55)

How to order:

FP 20•8 B0-13T1-L GD/GD-N


FORMULA 20

HYDRAULIC GEAR PUMPS ITALIAN STANDARD

13 T1-P

GAS STRAIGHT THREAD PORTS
British standard pipe parallel (55°) conforms to UNI - ISO 228

D 100-D47/0805



Standard version pumps have reversible rotation and internal drain.

The version with rear ports allow, removing the lateral plugs all possible combination ports.

Screw tightening torque Nm (lbf in)

V
70 ^{±7} (558 ÷ 682)

Pump type		A	B	C	Mass
		mm (in)	mm (in)		kg (lbs)
FP 20•8	B0-13T1-P GD/GD-N	129 (5.079)	105 (4.134)	G 1/2	4,8 (10.58)
FP 20•11,2		132,5 (5.217)	108,5 (4.272)		5 (11.03)
FP 20•16		142 (5.591)	112,5 (4.429)		5,2 (11.47)
FP 20•20		148,5 (5.846)	119 (4.685)		5,3 (11.69)
FP 20•25	B0-13T1-P GE/GE-N	156,5 (6.161)	112 (4.409)	G 3/4	5,9 (13.01)
FP 20•31,5		166,5 (6.555)	122 (4.803)		6 (13.23)
FP 20•36	B0-13T1-(L)P GE/GE-N	172,5 (6.791)	116,5 (4.587)		6,3 (13.89)
FP 20•40		178 (7.008)	122 (4.803)		6,6 (14.55)

How to order:

FP 20•11,2 B0-13T1-P GD/GD-N

01/08.2005


FORMULA 20

HYDRAULIC GEAR PUMPS ITALIAN STANDARD

43 TO - L

GAS STRAIGHT THREAD PORTS

British standard pipe parallel (55°) conforms to UNI - ISO 228



Standard version pumps have reversible rotation and internal drain.

Screw tightening torque Nm (lbf in)

v

70 $\pm$ 7 (558 $\div$ 682)

01/08.2005

Pump type		A	B	C	Mass
		mm (in)	mm (in)		kg (lbs)
FP 20•16	B0-43T0-L GD/GD-N	145,5 (5.728)	112,5 (4.429)	G 1/2	5,2 (11.47)
FP 20•20		152 (5.984)	119 (4.685)		5,3 (11.69)
FP 20•25		160 (6.299)	112 (4.409)		5,9 (13.01)
FP 20•31,5	B0-43T0-L GE/GE-N	170 (6.693)	122 (4.803)	G 3/4	6 (13.23)
FP 20•40		181 (7.126)	122 (4.803)		6,6 (14.55)

How to order:

FP 20•16 B0-43T0-L GD/GD-N


FORMULA 20

HYDRAULIC GEAR PUMPS ITALIAN STANDARD

43 TO - P

GAS STRAIGHT THREAD PORTS

British standard pipe parallel (55°) conforms to UNI - ISO 228



Standard version pumps have reversible rotation and internal drain.

The version with rear ports allow, removing the lateral plugs all possible combination ports.

Screw tightening torque Nm (lbf in)

v

70 $\pm$ 7 (558 $\div$ 682)

Pump type		A	B	C	Mass
		mm (in)	mm (in)		kg (lbs)
FP 20•16	B0-43T0-P GD/GD-N	142 (5.591)	112,5 (4.429)	G 1/2	5,2 (11.47)
FP 20•20		148,5 (5.846)	119 (4.685)		5,3 (11.69)
FP 20•25	B0-43T0-P GE/GE-N	156,5 (6.161)	112 (4.409)	G 3/4	5,9 (13.01)
FP 20•31,5	B0-43T0-(L)P GE/GE-N	166,5 (6.555)	122 (4.803)		6 (13.23)
FP 20•40		178 (7.008)	122 (4.803)		6,6 (14.55)

How to order

FP 20•16 B0-43T0-P GD/GD-N

01/08.2005


FORMULA 30

HYDRAULIC GEAR PUMPS ISO STANDARD

16 Z0

GAS STRAIGHT THREAD PORTS

British standard pipe parallel (55°) conforms to UNI - ISO 228



Multiple pumps available.

For the applications without radial load is available the light weight version without outboard bearing.

(For more information please consult our technical sales department).

Screw tightening torque Nm (lbf in)

V

70 ± 7 (558 $\div$ 682)

Pump type			A	B	C	D	Mass	
			mm (in)	mm (in)	IN	OUT	kg (lbs)	
01/08.2005	S D R B	0-16 Z0	L GD/GD-N	168,5 (6.634)	118,5 (4.665)	G 1/2	G 1/2	10,65 (23.48)
			L GE/GE-N	174,5 (6.870)	124,5 (4.902)	G 3/4	G 3/4	11,10 (24.48)
				179,5 (7.067)	124,5 (4.902)			11,56 (25.49)
				182,5 (7.185)	127,5 (5.020)			12,10 (26.68)
				185,5 (7.303)	130,5 (5.138)			12,30 (27.12)
				190,5 (7.500)	128,5 (5.059)			12,45 (27.45)
			L GF/GF-N	196,5 (7.736)	134,5 (5.295)	G1	G1	13,00 (28.67)
				204,5 (8.051)	135,5 (5.335)			13,70 (30.21)
				209,5 (8.248)	140,5 (5.531)			14,05 (30.98)
			L GG/GG-N	226,5 (8.917)	145,5 (5.728)	G 1 1/4	G 1 1/4	15,55 (34.29)
				242,5 (9.547)	161,5 (6.358)			17,05 (37.60)

Rotation: S=left - D=right - R=reversible - B=reversible internal drain

How to order:

FP 30•17 S0-16Z0-L GD/GD-N






FORMULA 30

HYDRAULIC GEAR PUMPS ITALIAN STANDARD


19 T

GAS STRAIGHT THREAD PORTS

British standard pipe parallel (55°) conforms to UNI - ISO 228



Flange T2
Only for rotation S-D



Screw tightening torque Nm (lbf in)

V
70 ⁺⁷ (558 ÷ 682)

D 100 - 113 / 0805

Pump type					A	B	C	D	Mass
					mm (in)	mm (in)	IN	OUT	kg (lbs)
FP 30•17	S D R B	0-19	T1	L GD/GD-N	150,5 (5.925)	100,5 (3.957)	G 1/2	G 1/2	9 (19.85)
FP 30•27					156,5 (6.161)	106,5 (4.193)			9,3 (20.51)
FP 30•34				L GE/GE-N	161,5 (6.358)	106,5 (4.193)	G 3/4	G 3/4	9,6 (21.17)
FP 30•38					164,5 (6.476)	109,5 (4.311)			9,8 (21.61)
FP 30•43					167,5 (6.594)	112,5 (4.429)			10 (22.05)
FP 30•51					172,5 (6.791)	110,5 (4.350)			10,3 (22.71)
FP 30•61			T2	L GF/GF-N	178,5 (7.028)	116,5 (4.587)	G1	G1	10,7 (23.59)
					186,5 (7.343)	117,5 (4.623)			10,9 (24.03)
FP 30•82			L GG/GF-N	191,5 (7.539)	122,5 (4.823)			11 (24.26)	
FP 30•100 (•)			L GG/GG-N	217 (8.543)	136 (5.354)	G 1 1/4	G 1 1/4	11,5 (25.36)	
FP 30•125 (•)				233 (9.173)	152 (5.984)			12,3 (27.12)	

Rotation: S=left - D=right - R=reversible - B=reversible internal drain
How to order:

(●) Only available in T1 version.

FP 30•17 S0-19T1-L GD/GD-N

01/08.2005


FORMULA 30

HYDRAULIC GEAR PUMPS ITALIAN STANDARD

13 T

GAS STRAIGHT THREAD PORTS

British standard pipe parallel (55°) conforms to UNI - ISO 228



Screw tightening torque Nm (lbf in)

V

70 ^{±7} (558 ÷ 682)

01/08.2005

Pump type				A	B	C	D	Mass
				mm (in)	mm (in)	IN	OUT	kg (lbs)
FP 30•61	S D R B	0-13	T1	L GF/GF-N	178,5 (7.028)	116,5 (4.587)	G 1	10,7 (23.59)
FP 30•82			T2	L GG/GF-N	191,5 (7.539)	122,5 (4.823)	G 1 1/4	11 (24.26)

Rotation: S=left - D=right - R=reversible - B=reversible internal drain
How to order:


FP 30•61S0-13T1-L GF/GF-N

FORMULA 30

HYDRAULIC GEAR PUMPS ITALIAN STANDARD

43 TO

GAS STRAIGHT THREAD PORTS
British standard pipe parallel (55°) conforms to UNI - ISO 228



Screw tightening torque Nm (lbf in)

V

70 ±7 (558 ÷ 682)

Pump type		A	B	C	D	Mass
		mm (in)	mm (in)	IN	OUT	kg (lbs)
FP 30•61	S	0-43-T0-L GF/GF-N	178,5 (7.028)	116,5 (4.587)	G 1	10,7 (23.59)
FP 30•82	R	0-43-T0-L GG/GF-N	191,5 (7.539)	122,5 (4.823)	G 1 1/4	11 (24.26)

Rotation: S=left - D=right - R=reversible - B=reversible internal drain
How to order:

FP 30•61S0-43T0-L GF/GF-N


01/08.2005

FORMULA 30

HYDRAULIC GEAR PUMPS SAE STANDARD

SAE

SAE STRAIGHT THREAD PORTS J514
American straight thread UNC-UNF 60° conforms to ANSI B 1.1.



To order see page 28 - 30

Screw tightening torque Nm (lbf in)

V

70 ±7 (558 ÷ 682)


01/08.2005

Pump type	A	B	C	D	Ports code		Mass
	mm (in)	mm (in)	IN	OUT	IN	OUT	kg (lbs)
FP 30•17 (•)	148 (5.827)	98 (3.858)	3/4-16 UNF-2B	3/4-16 UNF-2B	OB	OB	10,4 (22.93)
FP 30•27	154 (6.063)	104 (4.094)					10,8 (23.81)
FP 30•34	159 (6.260)	104 (4.094)	1-1/16-12 UN-2B		OD	OD	11,3 (24.92)
FP 30•38	162 (6.378)	107 (4.213)		1-1/16-12 UN-2B			11,5 (25.36)
FP 30•43	165 (6.496)	110 (4.331)					11,8 (26.02)
FP 30•51	170 (6.693)	108 (4.252)	1-5/16-12 UN-2B		OF		12 (26.46)
FP 30•61	176 (6.929)	114 (4.488)		1-3/16-12 UN-2B		OE	13 (28.67)
FP 30•73	184 (7.244)	115 (4.528)	1-5/8-12 UN-2B	1-5/16-12 UN-2B	OG	OF	13,4 (29.55)
FP 30•82	189 (7.441)	120 (4.724)					13,9 (30.65)


(•) Only available in version 2.

FORMULA 30 SAE VERSION


SAE



Version for applications without radial and axial load on the drive shaft.



Version for applications with low radial load and without axial load on the drive shaft.




Special version with independent shaft for applications with low radial load and without axial load on the drive shaft.

FORMULA 30 SAE END DRIVE SHAFTS

SAE

SAE "B" SPLINE


04



MAX 330 Nm (2921 lbf in) ♦

SAE "B" STRAIGHT


32



MAX 200 Nm (1770 lbf in) ♦

SAE "BB" SPLINE


05



MAX 500 Nm (4426 lbf in) ♦

SAE "BB" STRAIGHT

33




MAX 280 Nm (2478 lbf in) ♦

♦ For "2" version whichever end shaft, the max. torque applicable is M= 170 Nm (1505 lbf in)

01/08.2005

FORMULA 30 PERMISSIBLE RADIAL LOADING

SAE



X = Distance of the radial load result from the mounting flange.


Fatigue life (hours) $L_h = 1000$ [h]

Each curve has been obtained at

- (1) 1000 min⁻¹ (4) 2500 min⁻¹
- (2) 1500 min⁻¹ (5) 3000 min⁻¹
- (3) 2000 min⁻¹

VERSION

1-2



01/08.2005

HOW TO ORDER SINGLE PUMPS

1	2	3	4	5	6	7	8			
FP30•17	S	0	-	04	S3	-	L	OB/OB	-	N

1		Pump type	Code
1.05 (17,28) in³/rev (cm³/rev)			FP 30-17
1.63 (26,70) in³/rev (cm³/rev)			FP 30-27
2.11 (34,56) in³/rev (cm³/rev)			FP 30-34
2.40 (39,27) in³/rev (cm³/rev)			FP 30-38
2.68 (43,98) in³/rev (cm³/rev)			FP 30-43
3.16 (51,83) in³/rev (cm³/rev)			FP 30-51
3.74 (61,26) in³/rev (cm³/rev)			FP 30-61
4.50 (73,82) in³/rev (cm³/rev)			FP 30-73
4.98 (81,68) in³/rev (cm³/rev)			FP 30-82

2	Rotation	Code
Left		S
Ringht		D
Reversible		R
Reversible with internal drain		B

3	Version	Code
Without outboard bearing		0
With outboard bearing		1
With outboard bearing and indep. shaft		2

4	Drive shaft	Code
SAE "B" spline (13 teeth)		04
SAE "B" straight		32
SAE "BB" spline (15 teeth)		05
SAE "BB" straigh		33

5	Mounting flange	Code
SAE "B" 2-4 holes		S3

Code	Ports position	6
L	Side	

Code	PORTS IN/OUT	7
SAE STRAIGHT THREAD PORTS (ODT)		
Side	Pump type	
OB/OB	FP 30•17	
OD/OD	FP 30•27	
OD/OD	FP 30•34	
OD/OD	FP 30•38	
OF/OD	FP 30•43	
OF/OE	FP 30•51	
OF/OE	FP 30•61	
OG/OF	FP 30•73	
OG/OF	FP 30•82	

Code	Seals (b)	8
N	Buna N (standard)	
V	Viton	
N Bz	Buna N and Bronze thrust plates	
V Bz	Viton and Bronze thrust plates	

(b) Choose the seals according to the temperature shown on page 3

ORDER EXAMPLE

Standard pump **FP30.27S0-04S3-L0D/OD-N**

Special version pump **FP30.17S2-32S3-L0B/0B-V Bz**

01/08.2005


FORMULA 40

HYDRAULIC GEAR PUMPS ISO STANDARD

16 Z0

GAS STRAIGHT THREAD PORTS

British standard pipe parallel (55°) conforms to UNI - ISO 228



Screw tightening torque Nm (lbf in)

V

100 ±10 (797 ÷ 974)

01/08.2005

Pump type		A	B	C	D	Mass
		mm (in)	mm (in)	IN	OUT	kg (lbs)
FP 40•63	S D R B	L GF/GE-N	199 (7.835)	131 (5.157)	G 1	18,65 (41.12)
FP 40•73			203 (7.992)	135 (5.315)		19,30 (42.56)
FP 40•87		L GG/GF-N	208 (8.189)	140 (5.512)	G 1 1/4	19,75 (43.55)
FP 40•109			216 (8.504)	141 (5.551)		21 (46.31)
FP 40•133		L GH/GF-N	225 (8.858)	150 (5.906)	G1	22,10 (48.73)
FP 40•151			231 (9.094)	156 (6.142)		22,90 (50.49)

Rotation: S=left - D=right - R=reversible - B=reversible internal drain
How to order:


FP 40•63S0-16Z0-L GF/GE-N

FORMULA 40

HYDRAULIC GEAR PUMPS ITALIAN STANDARD

19 T

GAS STRAIGHT THREAD PORTS
British standard pipe parallel (55°) conforms to UNI - ISO 228



Screw tightening torque Nm (lbf in)

V

100 ± 10 (797 $\div$ 974)

Pump type				A	B	C	D	Mass	
				mm (in)	mm (in)	IN	OUT	kg (lbs)	
FP 40•63	S D R B	0-19	T1	L GF/GE-N	187,5 (7.382)	119,5 (4.705)	G 1	G 3/4	16,1 (35.50)
FP 40•73					191,5 (7.539)	123,5 (4.862)			16,5 (36.38)
FP 40•87			T2	L GG/GF-N	196,5 (7.736)	128,5 (5.059)	G 1 1/4		17 (37.49)
FP 40•109					204,5 (8.051)	129,5 (5.098)			18 (39.69)
FP 40•133				L GH/GF-N	213,5 (8.406)	138,5 (5.453)	G 1 1/2	G 1	19,5 (43.00)
FP 40•151						219,5 (8.642)			144,5 (5.689)

Rotation: S=left - D=right - R=reversible - B=reversible internal drain
How to order:

FP 40•63S0-19T1-L GF/GE-N


01/08.2005

FORMULA 40

HYDRAULIC GEAR PUMPS SAE STANDARD

SAE

SAE STRAIGHT THREAD PORTS J514
American straight thread UNC-UNF 60° conforms to ANSI B 1.1.



Screw tightening torque Nm (lbf in)

V

100 ±10 (797 ÷ 974)


To order see page 34 - 37

01/08.2005


Pump type	A	B	C	D	Ports code		Mass
	mm (in)	mm (in)	IN	OUT	IN	OUT	kg (lbs)
FP 40•63	188,5 (7.421)	120,5 (4.744)	1-5/16-12 UN-2B	1-1/16-12 UN-2B	OF	OD	19,5 (43.00)
FP 40•73	192,5 (7.579)	124,5 (4.902)					20 (44.10)
FP 40•87	197,5 (7.776)	129,5 (5.098)	1-5/8-12 UN-2B	1-5/16-12 UN-2B	OG	OF	20,5 (45.20)
FP 40•109	205,5 (8.091)	130,5 (5.138)					21 (46.31)
FP 40•133	214,5 (8.445)	139,5 (5.492)	1-7/8-12 UN-2B		OH		23 (50.72)
FP 40•151	220,5 (8.681)	145,5 (5.728)					25 (55.13)

FORMULA 40 SAE VERSION


SAE



Version for applications without radial and axial load on the drive shaft.



Version for applications with low radial load and without axial load on the drive shaft.




Special version with independent shaft for applications with low radial load and without axial load on the drive shaft.

FORMULA 40 SAE END DRIVE SHAFTS

SAE

SAE "C" SPLINE


06



MAX 900 Nm (7966 lbf in) ♦

SAE "C" STRAIGHT

34



MAX 600 Nm (5311 lbf in) ♦

♦For "2" version whichever and shaft, the max. torque applicable is $M = 600 \text{ Nm (5311 lbf in)}$


PUMP - VERSION - SHAFT AVAILABILITY TABLE

SAE

Pump type	VERSION			SHAFT
	0	1	2	
FP 40 • 63	06	06	06 - 34	
FP 40 • 73	06 - 34	06 - 34	06 - 34	
FP 40 • 87	06 - 34	06 - 34	06 - 34	
FP 40 • 109	06	06	06 - 34	
FP 40 • 133	06 - 34	06 - 34	06 - 34	
FP 40 • 151	06 - 34	06 - 34	06 - 34	

FORMULA 40 PERMISSIBLE RADIAL LOADING

SAE



X = Distance of the radial load result from the mounting flange.


Fatigue life (hours) $L_f = 1000$ [h]

Each curve has been obtained at

- (1) 1000 min^{-1}
- (2) 1500 min^{-1}
- (3) 2000 min^{-1}
- (4) 2500 min^{-1}
- (5) 3000 min^{-1}

VERSION

1-2



01/08.2005

HOW TO ORDER SINGLE PUMPS

1	2	3	4	5	6	7	8			
FP40•63	S	0	-	06	S8	-	L	OF/OD	-	N

1	Pump type	Code
3.75 (61,43) in ³ /rev (cm ³ /rev)		FP 40-63
4.43 (72,60) in ³ /rev (cm ³ /rev)		FP 40-73
5.28 (86,56) in ³ /rev (cm ³ /rev)		FP 40-87
6.64 (108,90) in ³ /rev (cm ³ /rev)		FP 40-109
8.18 (134,03) in ³ /rev (cm ³ /rev)		FP 40-133
9.20 (150,79) in ³ /rev (cm ³ /rev)		FP 40-151

2	Rotation	Code
Left		S
Right		D
Reversible		R
Reversible with internal drain		B

3	Version	Code
Without outboard bearing		0
With outboard bearing		1
With outboard bearing and indep. shaft		2

4	Drive shaft	Code
SAE "C" spline (14 teeth)		06
SAE "C" straight		34

5	Mounting flange	Code
SAE "C" 2-4 holes		S8

Code	Ports position	6
L	Side	

Code	PORTS IN/OUT	7
Side	Pump type	
OF/OD	FP 40•63	
OF/OD	FP 40•73	
OG/OF	FP 40•87	
OG/OF	FP 40•109	
OH/OF	FP 40•133	
OH/OF	FP 40•151	

Code	Seals (a)	8
N	Buna N (standard)	
V	Viton	
N Bz	Buna N and Bronze thrust plates	
V Bz	Viton and Bronze thrust plates	

(a) Choose the seals according to the temperature shown on page 3

ORDER EXAMPLE

Standard pump **FP40.63S0-06S8-LOF/OD-N**

Special version pump **FP40.63S2-34S8-LOF/OD-V Bz**

01/08.2005

MULTIPLE PUMPS

FORMULA series pumps can be coupled together in combination. Where input power requirement of each element varies, that with the greater requirement must be at the drive shaft end, and progressively smaller to the rear.

Features and performances are the same as the corresponding single pumps, but pressures must be limited by the transmissible torque of the drive and connecting shafts. To have appropriate data, use the formula below.

The maximum rotational speed is that of the lowest rated speed of the single units incorporated.

M	lbf in [Nm]	Torque
V	in ³ /rev [cm ³ /rev]	Displacement
Δp	psi [bar]	Pressure
$\eta_{hm} = \eta_m (V, \Delta p, n)$	(≈ 0,90)	Hydro-mechanical efficiency

$$\begin{aligned}
 \text{○ } M &= \frac{M_{\text{theor.}}}{\eta_{hm}} \quad [\text{Nm}] \\
 M_{\text{theor.}} &= \frac{\Delta p \text{ (bar)} \cdot V \text{ (cm}^3\text{/rev)}}{62,83}
 \end{aligned}$$





DRIVE SHAFT SELECTION

The torque absorbed from the shaft of the first pump results from the sum of the torques due to all single stages. The achieved value must not exceed the maximum torque limit given for the shaft of the first pump. Diagrams providing approximate selection data will be found on page 38.

Example

Let us consider a double pump FP40•63+ FP30•61. If we suppose that we have to work with the first pump at a pressure of 2900 psi (200 bar) and the second pump at a pressure of 2175 psi (150 bar), the graph 1 shows that the torque absorbed by FP40•63 is 1974 lbf in (223 Nm) and the graph 2 shows that the torque absorbed by FP30•61 is 1416 lbf in (160 Nm) [acceptable value because it don't exceed the maximum drive shaft torque that is 2478 lbf in (280 Nm), see page 42]. The torque to be transmitted by the first drive shaft will thus be 1974+1416=3390 lbf in (223+160= 383 Nm), this value must not exceed the shaft's maximum rated value.

ABSORBED TORQUE



01/08.2005

FORMULA 20

MULTIPLE PUMPS COMBINATION


FORMULA 20 + FORMULA 20

STANDARD VERSION

Front

Rear


D100-104/0600



FORMULA 20 END DRIVE SHAFT

ITALIAN STANDARD

13



MAX 280 Nm (2478 lbf in)

01/08.2005

FORMULA 30


MULTIPLE PUMPS COMBINATION

FORMULA 30 + FORMULA 30 STANDARD VERSION

Front

Intermediate

Rear




D 100-D26/1003

FORMULA 30 + KAPPA 20 STANDARD VERSION

Front

Rear




D 100-D78/0600

FORMULA 30 + POLARIS 20 STANDARD VERSION

Front

Rear




D 100-D79/0600

01/08.2005

FORMULA 30

MULTIPLE PUMPS SPECIAL COMBINATION

Special front section arranged to fit single pumps.
To order please consult our technical sales department.




D100-110/1003

01/08.2005

FORMULA 30 END DRIVE SHAFT

ITALIAN STANDARD


19



MAX 360 Nm (3186 lbf in)

ISO STANDARD

16



MAX 300 Nm (2655 lbf in)

FORMULA 40

MULTIPLE PUMPS COMBINATION


FORMULA 40 + FORMULA 40

STANDARD VERSION

Front

Intermediate

Rear




FORMULA 40 + FORMULA 30

STANDARD VERSION

Front

Rear




FORMULA 40 + FORMULA 20

STANDARD VERSION

Front

Rear



01/08.2005

FORMULA 40


MULTIPLE PUMPS COMBINATION

FORMULA 40 + KAPPA20

STANDARD VERSION

Front

Rear



110 Nm (974 lbf in)


D100-D76/0600

FORMULA 40 + POLARIS20

STANDARD VERSION

Front

Rear



110 Nm (974 lbf in)

D100-D77/0600


FORMULA 40 END DRIVE SHAFT

ITALIAN STANDARD


19

ISO STANDARD

16



MAX 400 Nm (3540 lbf in)




MAX 350 Nm (3098 lbf in)

SPLINE SAE STANDARD


06

STRAIGHT SAE STANDARD

34



MAX 900 Nm (7965 lbf in)



MAX 600 Nm (5310 lbf in)

01/08.2005






FORMULA 20

HYDRAULIC GEAR PUMPS ITALIAN STANDARD

13 T1

GAS STRAIGHT THREAD PORTS

British standard pipe parallel (55°) conforms to UNI - ISO 228



Screw tightening torque Nm (lbf in)

V

70 ±7 (558 ÷ 682)

01/08.2005

FORMULA 20
HYDRAULIC GEAR PUMPS ITALIAN STANDARD
13 T1

Pump type	A	B	C	D	E
	mm (in)	mm (in)	mm (in)	mm (in)	
FP 20•8	105 (4.272)	37,5 (1.476)	29 (1.142)	27,5 (1.083)	G 1/2
FP 20•11,2	108,5 (4.272)	38,5 (1.516)	32,5 (1.280)	27,5 (1.083)	
FP 20•16	112,5 (4.429)	43 (1.693)	36,5 (1.437)	32,5 (1.280)	
FP 20•20	119 (4.685)	43 (1.693)	43 (1.693)	33 (1.299)	
FP 20•25	112 (4.409)	58 (2.283)	36 (1.417)	48 (1.890)	G 3/4
FP 20•31,5	122 (4.803)	58 (2.283)	46 (1.811)	48 (1.890)	

The length of a triple pump is obtained with the sum of the following dimensions: **A+B+C+B+C+D**.

How to order a triple pump

(for double pump omit the intermediate pump)

Front pump	/	Intermediate pump	/	Rear pump	(1) Rotation	-	(2) Seals
FP20•11,2	/	20•11,2	/	20•11,2	S	-	

(1) S= Left - D= Right

(2) See page 3 (for Buna N seals no code)

01/08.2005







FORMULA 30

HYDRAULIC GEAR PUMPS ITALIAN STANDARD

19 T

ISO (Z0) and SAE (S3) version available (◆)

GAS STRAIGHT THREAD PORTS
British standard pipe parallel (55°) conforms to UNI - ISO 228



Screw tightening torque Nm (lbf in)

V

70 $\pm$ 7 (558 ÷ 682)

01/08.2005

FORMULA 30
HYDRAULIC GEAR PUMPS ITALIAN STANDARD
19 T

 (◆) Dimension "A"
 ISO and SAE version

mm (in)

A (Z0) A (19 T) + 18 (0.709)

A (S3) A (19 T) - 2,5 (0.098)

Pump type	A (19 T)	B	C	D	E	F	G	Ports code	
	mm (in)	mm (in)	mm (in)	mm (in)	IN	OUT	mm (in)	IN	OUT
FP 30•17	111,5 (4.390)	63 (2.480)	29 (1.142)	49 (1.929)					
FP 30•27	117,5 (4.626)	63 (2.480)	35 (1.378)	49 (1.929)					
FP 30•34	122,5 (4.823)	63(2.480)	40 (1.575)	49 (1.929)	G 3/4	G 3/4	130 (5.118)	GE	GE
FP 30•38	125,5 (4.941)	63(2.480)	43 (1.693)	49 (1.929)					
FP 30•43	128,5 (5.059)	63 (2.480)	46 (1.811)	49 (1.929)					
FP 30•51	125,5 (4.941)	71 (2.795)	43 (1.693)	57 (2.244)					
FP 30•61	132,5 (5.217)	70 (2.756)	50 (1.969)	56 (2.205)	G 1	G 1	135 (5.315)	GF	GF
FP 30•73	140,5 (5.531)	70 (2.756)	58 (2.283)	56 (2.205)					
FP 30•82 (●)	145,5 (5.728)	70 (2.756)	---	---	G 1 1/4			GG	

(●) Available only for front and intermediate section.

 The lenght of a triple pump is obtained with the sum of the following dimensions: **A+B+C+B+C+D**.

How to order a triple pump

(for double pump omit the intermediate pump)

Front pump	/	Intermediate pump	/	Rear pump	(1) Rotation	-	(2) Seals
FP30•17	/	30•17	/	30•17	S	-	

(1) S= Left - D= Right

(2) See page 3 (for Buna N seals no code)

01/08.2005



FORMULA 30

HYDRAULIC GEAR PUMPS ITALIAN STANDARD

19 T+KP20



ISO (Z0) and SAE (S3) version available (◆)

GAS STRAIGHT THREAD PORTS
British standard pipe parallel (55°) conforms to UNI - ISO 228




Shaft
UNI 8953 6x21x25 S
MAX. TORQUE 360 Nm
(3186 lbf in)


Flange T1



Flange T2



D100-D33/0805



01/08.2005

Screw tightening torque Nm (lbf in)

V	V1
70 ± 7 (558 $\div$ 682)	70 ± 7 (558 $\div$ 682)

FORMULA 30
HYDRAULIC GEAR PUMPS ITALIAN STANDARD
19 T+KP20

(◆) Dimension "A"
 ISO and SAE version

mm (in)

A (Z0) A (19 T) + 18 (0.709)

A (S3) A (19 T) - 2,5 (0.098)

Pump type	A (19 T)	B	C	D	E	Ports code	
	mm (in)	mm (in)	IN	OUT	mm (in)	IN	OUT
FP 30•17	111,5 (4.390)	63 (2.480)	G 3/4	G 3/4	130 (5.118)	GE	GE
FP 30•27	117,5 (4.626)	63 (2.480)					
FP 30•34	122,5 (4.823)	63 (2.480)					
FP 30•38	125,5 (4.941)	63 (2.480)					
FP 30•43	128,5 (5.059)	63 (2.480)	G 1	G 1	135 (5.315)	GF	GF
FP 30•51	125,5 (4.941)	71 (2.795)					
FP 30•61	132,5 (5.217)	70 (2.756)					
FP 30•73	140,5 (5.531)	70 (2.756)	G 1 1/4			GG	
FP 30•82	145,5 (5.728)	70 (2.756)					

Pump type	F	G	H	Ports code	
	mm (in)	mm (in)	IN	IN	OUT
KP 20•4	60 (2.362)	27,5 (1.083)	G 1/2 Depth 20 (0.787)	GD	GD
KP 20•6,3	62,5 (2.460)	27,5 (1.083)			
KP 20•8	65 (2.559)	27,5 (1.083))			
KP 20•11,2	68,5 (2.697)	27,5 (1.083)			
KP 20•14	67 (2.638)	33 (1.299)	G 3/4 Depth 22 (0.866)	GE	
KP 20•16	72,5 (2.854)	33 (1.299)			
KP 20•20	79 (3.110)	33 (1.299)			
KP 20•25	72 (2.835)	48 (1.890)			
KP 20•31,5	82 (3.228)	48 (1.890)			

How to order

Front pump/	/	Rear pump	-	Ports position	Ports IN/OUT	(1) Rotation	(2) Seals		
FP30•17	-	67	/	KP20•4	-	L	GD/GD	S	-

(1) S= Left - D= Right

(2) See page 3 (for Buna N seals no code)

01/08.2005







FORMULA 30

HYDRAULIC GEAR PUMPS ITALIAN STANDARD

19 T+PL20

ISO (Z0) and SAE (S3) version available (◆)

GAS STRAIGHT THREAD PORTS
British standard pipe parallel (55°) conforms to UNI - ISO 228



Screw tightening torque Nm (lbf in)

V	V1 (●)	V2
70 ± 7 (558 $\div$ 682)	70 ± 7 (558 $\div$ 682)	70 ± 7 (558 $\div$ 682)

(●) With cast iron front cover

01/08.2005

FORMULA 30
HYDRAULIC GEAR PUMPS ITALIAN STANDARD
19 T+PL20

(◆) Dimension "A"
 ISO and SAE version

mm (in)

A (Z0) A (19 T) + 18 (0.709)

A (S3) A (19 T) - 2,5 (0.098)

Pump type	A (19 T)	B	C	D	E	Ports code	
	mm (in)	mm (in)	IN	OUT	mm (in)	IN	OUT
FP 30•17	111,5 (4.390)	63 (2.480)					
FP 30•27	117,5 (4.626)	63 (2.480)					
FP 30•34	122,5 (4.823)	63 (2.480)	G 3/4	G 3/4	130 (5.118)	GE	GE
FP 30•38	125,5 (4.941)	63 (2.480)					
FP 30•43	128,5 (5.059)	63 (2.480)					
FP 30•51	125,5 (4.941)	71 (2.795)					
FP 30•61	132,5 (5.217)	70 (2.756)	G 1	G 1	135 (5.315)	GF	GF
FP 30•73	140,5 (5.531)	70 (2.756)					
FP 30•82	145,5 (5.728)	70 (2.756)	G 1 1/4			GG	

Pump type	F	G	H	Ports code	
	mm (in)	mm (in)	IN	IN	OUT
PLP 20•4	43,8 (1.722)	49,3 (1.941)			
PLP 20•6,3	45 (1.772)	50,5 (1.988)			
PLP 20•7,2	45,5 (1.791)	51 (2.008)			
PLP 20•8	46,3 (1.821)	51,8 (2.039)	G 1/2 Depth 17 (0.669)	GD	
PLP 20•9	46,9 (1.846)	52,4 (2.063)			
PLP 20•10,5	48,3 (1.900)	53,8 (2.118)			
PLP 20•11,2	48,5 (1.909)	54 (2.126)			
PLP 20•14	51 (2.008)	56,5 (2.224)			GD
PLP 20•16	52,8 (2.077)	58,3 (2.295)			
PLP 20•19	54,5 (2.146)	60 (2.553)			
PLP 20•20	56 (2.205)	61,5 (2.421)	G 3/4 Depth 18 (0.709)	GE	
PLP 20•24,5	58,8 (2.315)	64,3 (2.531)			
PLP 20•25	60 (2.362)	65,5 (2.579)			
PLP 20•27,5	61,4 (2.417)	66,9 (2.634)			
PLP 20•31,5	65 (2.559)	70,5 (2.776)			

How to order

Front pump/	/	Rear pump	-	Ports position	Ports IN/OUT	(1) Rotation	-	(2) Seals	
FP30•17	-	67	/	PLP20•4	-	L	GD/GD	S	-

(1) S= Left - D= Right

(2) See page 3 (for Buna N seals no code)

01/08.2005



FORMULA 40

HYDRAULIC GEAR PUMPS ITALIAN STANDARD

19 T



**ISO (Z0) version available (◆).
SAE (S8) version at page 62.**

GAS STRAIGHT THREAD PORTS
British standard pipe parallel (55°) conforms to UNI - ISO 228





Shaft
UNI 8953 6x21x25 S
MAX. TORQUE 400 Nm
(3540 lbf in)

Flange T1



Flange T2



Screw tightening torque Nm (lbf in)

V	V1
100 ± 10 (797 $\div$ 974)	100 ± 10 (797 $\div$ 974)

FORMULA 40
HYDRAULIC GEAR PUMPS ITALIAN STANDARD
19 T

 (◆) Dimension "A"
 ISO version

mm (in)

A (Z0) A (19 T) + 11,5 (0.453)

Pump type	A (19 T)	B	C	D	E	F	Ports code	
	mm (in)	mm (in)	mm (in)	mm (in)	IN	OUT	IN	OUT
FP 40•63	119,5 (4.705)	57,5 (2.264)	65,5 (2.579)	68 (2.677)	G 1	G 3/4	GF	GE
FP 40•73	123,5 (4.862)	57,5 (2.264)	69,5 (2.736)	68 (2.677)				
FP 40•87	128,5 (5.059)	57,5 (2.264)	74,5 (2.933)	68 (2.677)	G 1 1/4	G 1	GG	GF
FP 40•109	129,5 (5.098)	64,5 (2.539)	75,5 (2.972)	75 (2.953)				
FP 40•133	138,5 (5.453)	64,5 (2.539)	84,5 (3.327)	75 (2.953)	G 1 1/2		GH	
FP 40•151	144,5 (5.689)	64,5 (2.539)	90,5 (3.563)	75 (2.953)				

 The lenght of a triple pump is obtained with the sum of the following dimensions: **A+B+C+B+C+D**.

How to order a triple pump

(for double pump omit the intermediate pump)

Front pump	/	Intermediate pump	/	Rear pump	(1) Rotation	-	(2) Seals
FP40•63	/	40•63	/	40•63	S	-	

(1) S= Left - D= Right

(2) See page 3 (for Buna N seals no code)

01/08.2005






FORMULA 40

HYDRAULIC GEAR PUMPS ITALIAN STANDARD

19 T+FP30

ISO (Z0) and SAE (S8) version available (◆)

GAS STRAIGHT THREAD PORTS
British standard pipe parallel (55°) conforms to UNI - ISO 228



Screw tightening torque Nm (lbf in)

V	V1
100 ± 10 (797 ÷ 974)	70 ± 7 (558 ÷ 682)

FORMULA 40
HYDRAULIC GEAR PUMPS ITALIAN STANDARD
19 T+FP30

(◆) Dimension "A"
 ISO and SAE version

mm (in)

A (Z0)	A (19 T) + 11,5 (0.453)
A (S8)	A (19 T) + 1 (0.039)

Pump type	A (19 T)	B	C	D	Ports code	
	mm (in)	mm (in)	IN	OUT	IN	OUT
FP 40•63	119,5 (4.705)	84,5 (3.327)	G 1	G 3/4	GF	GE
FP 40•73	123,5 (4.862)	84,5 (3.327)				
FP 40•87	128,5 (5.059)	84,5 (3.327)	G 1 1/4	G 1	GG	GF
FP 40•109	129,5 (5.098)	91,5 (3.602)				
FP 40•133	138,5 (5.453)	91,5 (3.602)	G 1 1/2		GH	
FP 40•151	144,5 (5.689)	91,5 (3.602)				

Pump type	E	F	G	H
	mm (in)	mm (in)	IN	IN
FP 30•17	100,5 (5.925)	50 (1.969)	G 1/2	G 1/2
FP 30•27	106,5 (4.193)	50 (1.969)		
FP 30•34	106,5 (4.193)	55 (2.165)	G 3/4	G 3/4
FP 30•38	109,5 (4.311)	55 (2.165)		
FP 30•43	112,5 (4.429)	55 (2.165)		
FP 30•51	110,5 (4.350)	62 (2.441)		
FP 30•61	116,5 (4.587)	62 (2.441)	G 1	G 1
FP 30•73	117,5 (4.623)	69 (2.717)		
FP 30•82	122,5 (4.823)	69 (2.717)	G 1 1/4	

How to order

Front pump	/	Rear pump	(1) Rotation	-	(2) Seals
FP40•63	-	53	/	FP30•17	S

(1) S= Left - D= Right

(2) See page 3 (for Buna N seals no code)

01/08.2005





FORMULA 40

HYDRAULIC GEAR PUMPS ITALIAN STANDARD

19 T+FP20


ISO (Z0) and SAE (S8) version available (◆)

GAS STRAIGHT THREAD PORTS
British standard pipe parallel (55°) conforms to UNI - ISO 228



Screw tightening torque Nm (lbf in)

V	V1
100 ± 10 (797 ÷ 974)	70 ± 7 (558 ÷ 682)



01/08.2005

FORMULA 40
HYDRAULIC GEAR PUMPS ITALIAN STANDARD
19 T+FP20

(◆) Dimension "A"
 ISO and SAE version

mm (in)

A (Z0)	A (19 T) + 11,5 (0.453)
A (S8)	A (19 T) + 1 (0.039)

Pump type	A (19 T)	B	C	D	Ports code	
	mm (in)	mm (in)	IN	OUT	IN	OUT
FP 40•63	119,5 (4.705)	84,5 (3.327)	G 1	G 3/4	GF	GE
FP 40•73	123,5 (4.862)	84,5 (3.327)				
FP 40•87	128,5 (5.059)	84,5 (3.327)	G 1 1/4	G 1	GG	GF
FP 40•109	129,5 (5.098)	91,5 (3.602)				
FP 40•133	138,5 (5.453)	91,5 (3.602)	G 1 1/2		GH	
FP 40•151	144,5 (5.689)	91,5 (3.602)				

Pump type	E	F	G	H
	mm (in)	mm (in)	IN	IN
FP 20•8	105 (4.134)	27,5 (1.083)	G 1/2	G 1/2
FP 20•11,2	108,5 (4.272)	27,5 (1.083)		
FP 20•16	112,5 (4.429)	33 (1.299)		
FP 20•20	119 (4.685)	33 (1.299)		
FP 20•25	112 (4.409)	48 (1.890)	G 3/4	G 3/4
FP 20•31,5	122 (4.803)	48 (1.890)		
FP 20•36	116,5 (4.587)	59 (2.323)		
FP 20•40	122 (4.803)	59 (2.323)		

01/08.2005

How to order

Front pump	/	Rear pump	(1) Rotation	-	(2) Seals
FP40•63	-	54	/	FP20•11,2	S

(1) S= Left - D= Right

(2) See page 3 (for Buna N seals no code)



FORMULA 40

HYDRAULIC GEAR PUMPS ITALIAN STANDARD

19 T+KP20



ISO (Z0) and SAE (S8) version available (◆)

GAS STRAIGHT THREAD PORTS
British standard pipe parallel (55°) conforms to UNI - ISO 228




Shaft
UNI 8953 6x21x25 S
MAX. TORQUE 400 Nm
(3540 lbf in)

Flange T1




Flange T2



Screw tightening torque Nm (lbf in)

V	V1
100 ± 10 (797 ÷ 974)	70 ± 7 (558 ÷ 682)



01/08.2005

FORMULA 40
HYDRAULIC GEAR PUMPS ITALIAN STANDARD
19 T+KP20

(◆) Dimension "A"
ISO and SAE version

mm (in)

A (Z0)	A (19 T) + 11,5 (0.453)
A (S8)	A (19 T) + 1 (0.039)

Pump type	A (19 T)	B	C	D	Ports code	
	mm (in)	mm (in)	IN	OUT	IN	OUT
FP 40•63	119,5 (4.705)	84,5 (3.327)	G 1	G 3/4	GF	GE
FP 40•73	123,5 (4.862)	84,5 (3.327)				
FP 40•87	128,5 (5.059)	84,5 (3.327)	G 1 1/4	G 1	GG	GF
FP 40•109	129,5 (5.098)	91,5 (3.602)				
FP 40•133	138,5 (5.453)	91,5 (3.602)	G 1 1/2		GH	
FP 40•151	144,5 (5.689)	91,5 (3.602)				

Pump type	F	G	H	Ports code	
	mm (in)	mm (in)	IN	IN	OUT
KP 20•4	60 (2.362)	27,5 (1.083)	G 1/2 Depth 20 (0.787)	GD	GD
KP 20•6,3	62,5 (2.460)	27,5 (1.083)			
KP 20•8	65 (2.559)	27,5 (1.083)			
KP 20•11,2	68,5 (2.697)	27,5 (1.083)			
KP 20•14	67 (2.638)	33 (1.299)	G 3/4 Depth 22 (0.866)	GE	GE
KP 20•16	72,5 (2.854)	33 (1.299)			
KP 20•20	79 (3.110)	33 (1.299)			
KP 20•25	72 (2.835)	48 (1.890)			
KP 20•31,5	82 (3.228)	48 (1.890)			

01/08.2005

How to order

Front pump	/	Rear pump	-	Ports position	Ports IN/OUT	(1) Rotation	-	(2) Seals	
FP40•63	-	52	/	KP20•4	-	L	GD/GD	S	-

(1) S= Left - D= Right

(2) See page 3 (for Buna N seals no code)


FORMULA 40

HYDRAULIC GEAR PUMPS ITALIAN STANDARD


19 T+PL20

ISO (Z0) and SAE (S8) version available (◆)



GAS STRAIGHT THREAD PORTS
British standard pipe parallel (55°) conforms to UNI - ISO 228




Shaft
UNI 8953 6x21x25 S
MAX. TORQUE 400 Nm
(3540 lbf in)



Flange T1




Flange T2



Screw tightening torque Nm (lbf in)

V	V1 (●)	V2
100 ± 10 (797 $\div$ 974)	70 ± 7 (558 $\div$ 682)	70 ± 7 (558 $\div$ 682)

(●) With cast iron front cover.



01/08.2005

FORMULA 40
POMPE A INGRANAGGI UNIFICAZIONE ITALIANA
19 T+PL20

(◆) Dimension "A"
 ISO and SAE version

mm (in)

A (Z0) A (19 T) + 11,5 (0.453)

A (S8) A (19 T) + 1 (0.039)

Pump type	A (19 T)	B	C	D	Ports code	
	mm (in)	mm (in)	IN	OUT	IN	OUT
FP 40•63	119,5 (4.705)	84,5 (3.327)	G 1	G 3/4	GF	GE
FP 40•73	123,5 (4.862)	84,5 (3.327)				
FP 40•87	128,5 (5.059)	84,5 (3.327)	G 1 1/4	G 1	GG	GF
FP 40•109	129,5 (5.098)	91,5 (3.602)				
FP 40•133	138,5 (5.453)	91,5 (3.602)	G 1 1/2		GH	
FP 40•151	144,5 (5.689)	91,5 (3.602)				

Pump type	E	F	G	Ports code	
	mm (in)	mm (in)	mm (in)	IN	OUT
PLP 20•4	43,8 (1.722)	49,3 (1.941)	G 1/2 Depth 17 (0.669)	GD	GD
PLP 20•6,3	45 (1.772)	50,5 (1.988)			
PLP 20•7,2	45,5 (1.791)	51 (2.008)			
PLP 20•8	46,3 (1.821)	51,8 (2.039)			
PLP 20•9	46,9 (1.846)	52,4 (2.063)			
PLP 20•10,5	48,3 (1.900)	53,8 (2.118)			
PLP 20•11,2	48,5 (1.909)	54 (2.126)			
PLP 20•14	51 (2.008)	56,5 (2.224)	G 3/4 Depth 18 (0.709)	GE	GE
PLP 20•16	52,8 (2.077)	58,3 (2.295)			
PLP 20•19	54,5 (2.146)	60 (2.553)			
PLP 20•20	56 (2.205)	61,5 (2.421)			
PLP 20•24,5	58,8 (2.315)	64,3 (2.531)			
PLP 20•25	60 (2.362)	65,5 (2.579)			
PLP 20•27,5	61,4 (2.417)	66,9 (2.634)			
PLP 20•31,5	65 (2.559)	70,5 (2.776)			

01/08.2005

How to order

Front pump/	/	Rear pump	-	Ports position	Ports IN/OUT	(1) Rotation	-	(2) Seals	
FP40•63	-	52	/	PLP20•4	-	L	GD/GD	S	-

(1) S= Left - D= Right


(2) See page 3 (for Buna N seals no code)

FORMULA 40

HYDRAULIC GEAR PUMPS SAE STANDARD

SAE

SAE STRAIGHT THREAD PORTS J514
American straight thread UNC-UNF 60° conforms to ANSI B 1.1



Screw tightening torque Nm (lbf in)	
V	V1
100 ± 10 (797 $\div$ 974)	100 ± 10 (797 $\div$ 974)


Pump type	A	B	C	D	E	F	Ports code	
	mm (in)	mm (in)	mm (in)	mm (in)	IN	OUT	IN	OUT
FP 40•63	120,5 (4.744)	57,5 (2.264)	65,5 (2.579)	68 (2.677)	1-5/16-12 UN-2B	1-1/16-12 UN-2B	OF	OD
FP 40•73	124,5 (4.902)	57,5 (2.264)	69,5 (2.736)	68 (2.677)				
FP 40•87	129,5 (5.098)	57,5 (2.264)	74,5 (2.933)	68 (2.677)	1-5/8-12 UN-2B	1-5/16-12 UN-2B	OG	OF
FP 40•109	130,5 (5.138)	64,5 (2.539)	75,5 (2.972)	75 (2.953)				
FP 40•133	139,5 (5.492)	64,5 (2.539)	84,5 (3.327)	75 (2.953)	1-7/8-12 UN-2B		OH	
FP 40•151	145,5 (5.728)	64,5 (2.539)	90,5 (3.563)	75 (2.953)				

The length of a triple pump is obtained with the sum of the following dimensions: **A+B+C+B+C+D**.


01/08.2005

FORMULA 40 SAE VERSION


SAE



Version for applications without radial and axial load on the drive shaft.



Version for applications with low radial load and without axial load on the drive shaft




Special version with independent shaft for applications with low radial load and without axial load on the drive shaft.

FORMULA 40 SAE END DRIVE SHAFT

SAE

SAE "C" SPLINE


06



MAX 900 Nm (7966 lbf in) ♦

SAE "C" STRAIGHT

34



MAX 600 Nm (5311 lbf in) ♦

♦For "2" version whichever and shsft, the max. torque applicable is M= 600 Nm (5311 lbf in)

PUMP - VERSION - SHAFT AVAILABILITY TABLE

SAE

Pump type	VERSION			SHAFT
	0	1	2	
FP 40 • 63	06	06	06 - 34	
FP 40 • 73	06 - 34	06 - 34	06 - 34	
FP 40 • 87	06 - 34	06 - 34	06 - 34	
FP 40 • 109	06	06	06 - 34	
FP 40 • 133	06 - 34	06 - 34	06 - 34	
FP 40 • 151	06 - 34	06 - 34	06 - 34	

HOW TO ORDER MULTIPLE PUMPS

1	2	3	4	5	6	7	8
FP40•63	-	06	S8	-	L	OF/OD	/
Front pump							
40•63	-		L	OF/OD	/		
Intermediate pump							
40•63	-		L	OF/OD	-	S	-
						0	N
Rear pump							

1	Pump type	Code
3.75 (61,43) in ³ /rev (cm ³ /rev)		FP 40•63
4.43 (72,60) in ³ /rev (cm ³ /rev)		FP 40•73
5.28 (86,56) in ³ /rev (cm ³ /rev)		FP 40•87
6.64 (108,90) in ³ /rev (cm ³ /rev)		FP 40•109
8.18 (134,03) in ³ /rev (cm ³ /rev)		FP 40•133
9.20 (150,79) in ³ /rev (cm ³ /rev)		FP 40•151

2	Drive shaft	Code
SAE "C" spline (14 teeth)		06
SAE "C" straigh		34

3	mounting flange	Code
SAE "C" 2-4 holes		S8

4	Ports position	Code
Side		L

Code	Ports IN/OUT	5
SAE STRAIGHT THREAD PORTS (ODT)		
Side	Pump type	
OF/OD	FP 40•63	
OF/OD	FP 40•73	
OG/OF	FP 40•87	
OG/OF	FP 40•109	
OH/OF	FP 40•133	
OH/OF	FP 40•151	

Code	Rotation	6
S	Left	
D	Right	

Code	Version	7
0	Without outboard bearing	
1	With outboard bearing	
2	With outboard bearing and indep. shaft	

Code	Seals (a)	8
N	Buna N (standard)	
V	Viton	
N Bz	Buna N and Bronze thrust plates	
V Bz	Viton and Bronze thrust plates	

a) Choose the seals according to the temperature shown on page 3

01/08.2005

ORDER EXAMPLE

Triple pump

FP40•63-06S8-LOF/OD/ 40•63-LOF/OD/40•63-LOF/OD S-0-N

PORTS CONNECTORS TIGHTENING TORQUE



Tightening torque for low pressure side port.



Tightening torque for high pressure side port [values obtained at 350 bar (5075 psi)]

For reversible rotation, please consult only the tightening torque for high pressure side port.

Replaces: 01/08.2005

GAS STRAIGHT THREAD PORTS

BSPP

CODE				
	Nm	(lbf in)	Nm	(lbf in)
GC (◆)	15 ⁺¹	133 ÷ 142	—	—
GD	20 ⁺¹	177 ÷ 186	50 ^{+2,5}	443 ÷ 465
GE	30 ^{+2,5}	266 ÷ 288	90 ⁺⁵	797 ÷ 841
GF	50 ^{+2,5}	443 ÷ 465	130 ⁺¹⁰	1151 ÷ 1239
GG 	70 ⁺⁵	620 ÷ 664	170 ⁺¹⁵	1505 ÷ 1637
GH	70 ⁺⁵	620 ÷ 664	—	—

SAE STRAIGHT THREAD PORTS J514

ODT


CODICE				
	Nm	(lbf in)	Nm	(lbf in)
OA (◆)	15 ⁺¹	133 ÷ 142	—	—
OB	20 ⁺¹	177 ÷ 186	45 ^{+2,5}	398 ÷ 420
OD	40 ^{+2,5}	354 ÷ 376	120 ⁺¹⁰	1062 ÷ 1151
OE	50 ^{+2,5}	443 ÷ 465	145 ⁺¹⁰	1283 ÷ 1372
OF	60 ⁺⁵	531 ÷ 575	170 ⁺¹⁰	1505 ÷ 1593
OG	70 ⁺⁵	620 ÷ 664	—	—
OH	100 ⁺⁵	885 ÷ 929	—	—

(◆) Drain port: FORMULA 30 and FORMULA 40 rear drain (R).

 03/05.2013

BEARING SUPPORT FOR COUPLING TO ZF P.T.O.(ISO Standard)

SL9 - SR9





The bearing support allows FORMULA Italian standard pumps to be coupled to P.T.O. of commercial vehicles.



Ordering code	Max. radial load 24 mm (0.945 in) from mounting face (Fr)	Mass
	N	kg (lbs)
SL9	—	2,7 (5.95)
SR9	Low load	

01/08.2005

KIT to assemble FP20 - 13 T1 and FP30 - 13 T pumps with support

Part	Q.ty	Description	Ordering code
	3	Stud M 10x30 UNI 5911 Nut M 10 Washer 10 DIN 7980	
	1	Gasket	KIT 10 - A
	1	Splined coupling MA 6x21x25 UNI 8953 - A 22x19 DIN 5482 L= 31	


KIT to assemble FP30 - 19 T and FP40 - 19 T pumps with support

Part	Q.ty	Description	Ordering code
	3	Stud M 10x30 UNI 5911 Nut M 10 UNI 7473	
	1	Gasket	KIT 17 - A
	1	Splined coupling MA 6x21x25 UNI 8953 L= 31	

01/08.2005


APPLICATIONS FOR FORMULA PUMPS WITH ZF P.T.O.(ISO STANDARD)

D100-108/1003



The FORMULA pumps in the application with radial load can be directly connected to the “ZF” P.T.O.


D100-D85/0493




The FORMULA pumps in the application with radial load can be directly connected to the “ZF” P.T.O. with straight teeth gear using the SR9 support.

01/08.2005

APPLICATIONS FOR FORMULA PUMPS WITH ZF P.T.O.(ISO STANDARD)



The FORMULA pumps in the application without radial load can be directly connected to the "ZF" P.T.O. only on self sealed version using the SL9 support.



Use SL9 support to apply the universal joint.

01/08.2005




D 100-D86/0493

CHANGING ROTATION

Example of changing rotation: from FP30 pump counterclockwise to clockwise

To change rotation of unidirectional pumps is necessary to operate in the following way:

1. Clean the pump externally with care.
2. Loosen, and remove, the clamp bolts (1)
3. Coat the sharp edges of the drive shaft (4) with adhesive tape and smear a layer of clean grease on the shaft end extension to avoid damaging the lip of the shaft seal when removing the mounting flange.
4. Remove the mounting flange (2), taking care to keep the flange as straight as possible during removal. If the flange is stuck, tap around the edge with a fibre or rubber mallet in order to break away from the body. Ensure that while removing the front mounting flange, the drive shaft and other components remain position.
5. Ease the drive gear (4) up to facilitate removal the front plate (3), taking care that the precision ground surfaces do not become damaged, and remove the drive gear.
6. Remove the driven gear (5) without overturning. The rear plate has not to be removed.
7. Re-locate the driven gear (5) in the position previously occupied by the drive gear (4)
8. Re-locate the drive gear (4) in the position previously occupied by the driven gear (5)
9. Replace the front plate (3) in its original position.
10. Remove the grub screw (6) from the mounting flange (2) and re-locate it in the other threaded hole in the same flange.
11. Gently wipe the machined surface of the mounting flange (2) and the body with a flat hand stone.
12. Refit the front mounting flange (2) turned 180° from its original position.
13. Refit the clamp bolts (1) with the washers and tighten in a crisscross pattern to a torque value of $70 \pm 7 \text{ Nm}$ ($558 \div 682 \text{ lbf in}$).
14. Check that the pump rotates freely when the drive shaft (4) is turned by hand. If not a pressure plate seal may be pinched.
15. The pump is ready for installation with the original rotation reversed.



INSTRUCTIONS

INSTALLATION

The direction of rotation of single-rotation pumps must be the same as that of the drive shaft. Check that the coupling flange correctly aligns the transmission shaft and the pump shaft, the connection do not generate an axial or radial load on the pump shaft

TANK

Tank capacity must be sufficient for the system's operating conditions (~ 3 times the amount of oil in circulation) to avoid overheating of the fluid. A heat exchanger should be installed if necessary. The intake and return lines in the tank must be spaced apart (by inserting a vertical divider) to prevent the return-line oil from being taken up again immediately.

LINES

The lines must have a major diameter which is at least as large as the diameter of pump ports, and must be perfectly sealed. To reduce loss of power, the lines should be as short as possible, reducing the sources of hydraulic resistance (elbow, throttling, gate valves, etc.) to a minimum. A length of flexible tubing is recommended to reduce the transmission of vibrations. All return lines must end below the minimum oil level, to prevent foaming. Before connecting the lines, remove any plugs and make sure that the lines are perfectly clean

FILTERS

We recommend filtering the entire system flow. Filters on suction and return line must be fitted in according to the contamination class as indicated in the first pages of the catalogue. Casappa recommends to use its own production filters:

HYDRAULIC FLUID

Use hydraulic fluid conforming to the table as specified in the first pages of the catalogue. Avoid using mixtures of different oils which could result in decomposition and reduction of the oil's lubricating power.

STARTING UP

Check that all circuit connections are tight and that the entire system is completely clean. Insert the oil in the tank, using a filter. Bleed the circuit to assist in filling. Set the pressure relief valves to the lowest possible setting. Turn on the system for a few moments at minimum speed, then bleed the circuit again and check the level of oil in the tank. Then gradually increase the pressure and speed of rotation until the pre-set operating levels as specified in the catalogue are attained.

PERIODICAL CHECKS - MAINTENANCE

Keep the outside surface clean especially in the area of the drive shaft seal. In fact, abrasive powder can accelerate wear on the seal and cause leakage. Replace filters regularly to keep the fluid clean. The oil level must be checked and oil replaced periodically depending on the system's operating conditions.



01/08.2005

Our policy is one of continuous improvement in product. Specification of items may, therefore, be changed without notice.